

Estd. 1964



**YSI-060** 

Semi Automatic Manual Rotary Microtome



# Semi Automatic Rotary Microtome Programmable

The New Unimeditrek UNIYSI-060 Semi Automatry microtome characterizes the faultless combination of cost effective competence and user comfort. It is the instrument of choice for clinical histology and histopathology application, as well as for industry quality assurance.

Manual sectioning is enhanced by the high precision motorized specimen feed, which fallout in efficient operation with utmost section reproducibility. Improved user comfort results in maximum workspace efficiency and high throughput.

## **Well located storage Area**

An incorporated storage tray makes certain subsidiary tools are in hand at all the times.

#### **Safety During Sectioning**

Protection is assured by incorporated black finger protection guard of the knife holder that exceptionally safeguards the blade edge. When used correctly the integrated finger protection guard rules out potential injuries because it can even remain on the blade edge during sectioning.

#### **Contented Operation**

All functions are controlled via touch sensitive buttons located on both sides of the block holder.

## **Trouble Free Operation**

Ergonomics and user comfort are key concern for the placement of coarse feed wheel, which is located close to the operator. The mechanical trimming function, conveniently positioned next to coarse feed wheel, purge the need to turn coarse feed wheel during trimming.

## **Spacious Section Waste Tray**

The spacious section waste tray consistently gathers sectioning wreckage. Accurate Specimen orientation with clear zero reference point. This new orientation technique sets innovative standards of precision and is very effortless to operate. Calibrated controls make it easy to fiddle with a specified by assessable variable on the x/y axis for re—cuts.

## **Imaginative Knife holder adjustment**

The complete width of the knife could be used by using straight forward blade fastening mechanism Using the complete knife edge is cost effective, particularly in laboratories with high specimen throughout.

Suitable to work on 220V, single phase, 50 Hz, AC supply.



Manufactured By:

#### **Technical Data**

Section Thickness Setting range : Section Thickness Setting range

0.5mm-90mm

Setting Value : From 0.5mm-1mm in 0.5mm increments

: From 1mm-99mm in 1mm increments

Trimming Section : Thickness setting Range 0.5mm-99mm

Setting Values : From 0.5mm-1mm in 0.5 mm increments

From 1mm-99 mm in 1mm increments

Specimen Retraction

Motorized Operation : Varying with section speed

Horizontal Specimen Feed : Approx. 30mm

Vertical Specimen Feed : Approx. 60mm

Sectioning Modes : 1Manual Mode

 $\begin{tabular}{lll} \mbox{Maximum Specimen Size} & : & 50mm (L) \times 60mm (H) \times 40mm (W) \\ \mbox{Specimen Orientation} & : & \mbox{Horizontal:8°, Vertical:8°, Z:360°} \\ \end{tabular}$ 

Operating Voltages : Nominal Supply Voltages

100V/120V/230V/240V

Nominal Frequency : 50/60Hz.

Dimensions basic instruments

Width (Including handwheel) : 390mm

Depth (Including waste tray) : 510mm

Height (with storage cover) : 305mm

Weight (with accessories) : Approx, 26Kg.

#### **General**

- Compact Ergonomic Overall Design.
- Accurate Specimen orientation with zero point reference.
- Easy shift between trimming and sectioning operation.
- Two motorized forward specimen coarse feed speeds.
- Automatic Specimen retraction.
- Section-Handed function universal cassette clamp.
- Absolutely new knife holder replica for disposable blades, with finger guard in contrasting color.
- User safety incorporated into overall design.
- Smoothing-running hand lateral movement.
- Engonomically optimized hand wheel handle.
- Communication display incorporated in instrument housing enclosed micrometer mechanism.
- Spacious section waster tray.
- Wide range of accessories.
- Automatic retraction.

# **Supplied Complete With**

- Cassette holder
- Knife holder base
- Object orientation unit
- Section waste tray
- Disposable blade (Pack of 50 Blades)

